SUREGUARD PRODUCTS CO. 492 WHITE SAND ROAD POPLARVILLE, MS 39470 CONTACT: DARRYL MILLER



# MATERIAL SAFETY DATA SHEET ATF DexronIII/Mercon

### PRODUCT IDENTIFICATION

Trade Name:

Dexron III Mercon ATF

Date Revised: July 28, 1995

synonyms/product Code: N.A.

mical Name:

Petroleum Mineral Oil

amily Description: A complex combination of hydrocarbons from a petroleum fraction obtained by solven

crystallization plus additives.

OT Hazard Class: Not Applicable

### COMPOSITION

Occupational Exposure Limits\*

duct	CAS Number	Wt%	OSHA PEL	ACGII TLV	Other	<u>Units</u>	
Dexron III con ATF	Mixture	100	N.A.	N.A.			
	the same of the sa	The second secon	the state of the s				
redient(s): /ent Dewaxed vy Paraffinic	64742-65-0	85	5	5	10 STEL	mg/m³**	

<sup>\* = 8-</sup>Hr. TWA unless otherwise specified.

N.A. = Not Available

STEL = Short Term Exposure Limit; 15 minutes.

<sup>\*\* =</sup> As'mineral oil Mist

<sup>\*\*\* =</sup> All ingredients in this product are listed in the T.S.C.A. Inventory.

#### PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg:

Viscosity (method, temp):

N.A.

Melting Point: 40F

Vapor Pressure mmHg @ 100F:

N.A.

Vapor Density (air=1): N.A.

Solubility in H2O %:

Nil.

pH: N.A.

Specific Gravity (H2O): % Volatile by Volume:

0.8762

Evaporation Rate (ethyl ether =1):

N.A.

Odor: Slight hydrocarbon odor

7.10 cst,100C

Appearance: Red Liquid

N.A. = Not Available

#### FIRE AND EXPLOSION DATA

Flash Point:

415F COC

Flammable Limits in Air % by Vol.

Lower: N.A.

Upper: N.A.

Autoignition Temperature:

Extinguishing Media:

Dry chemical, foam, carbon dioxide or water spray.

Special Fire Fighting Procedure:

Water spray may be ineffective on flames but should be used to keep fireexposed containers cool, Firefighters should wear self-contained breathing

apparatus.

usual Fire or Explosion Hazard:

May ignite when sufficient heat is applied.

#### REACTIVITY DATA

Stability:

Stable

Hazardous Polymerization:

Will not occur.

Conditions to Avoid/Incompatibility:

Hazardous Decomposition Products:

Strong oxidizing agents, heat, spark, flame and build-up of static electricity. Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and

combustion

products of sulfur and nitrogen.

#### HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No

IARC Monographs: No

OSHA Regulated: No

Occupational Exposure Limits:

See COMPOSITION section.

Effects of Overexposure:

'ute:

Eyes:

The heavy paraffinic petroleum distillate fraction of this product is believed to b minimally irritating.

Dexron III Mercon ATF

Page 3 of 4

Skin:

The heavy paraffinic petroleum distillate fraction of this product is believed to be minimally irritating.

Inhalation:

The inhalation hazards of this products components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits.

Ingestion:

Ingestion hazards range from practically non-toxic to minimally toxic for the components of this product. If vomiting occurs, product is an aspiration hazard.

Chronic: Frequent or prolonged contact may cause skin irritation.

for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity in experimental animals of used oil.

Additional Medical and Toxicological Information: May aggravate pre-existing dermatitis. The International Agency

## EMERGENCY FIRST AID PROCEDURES

Eye Contact: Skin Contact:

Inhalation:

Ingestion:

Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical help.

Flush thoroughly with water for at least 15 minutes. Get medical attention.

Remove to fresh air. Apply artificial respiration if not breathing. Get medical

attention.

Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head

lower than hips to prevent aspiration.

## SPECIAL PROTECTION INFORMATION

Eye Protection:

Inhalation:

Ventilation:

Remove contact lenses and wear chemical safety goggles where contact with liquid or mist may occur.

Skin Protection:

Wear impervious gloves when contact with skin may occur. Use face shields

where splashing may occur.

levels.

Use approved respiratory protective equipment for cleaning large spills or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels. Provide adequate ventilation to keep mist or vapors below occupational exposure

## SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures:

Remove sources of heat or ignition including internal combustion engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with and absorbent. Use approved respirator where occupational exposure limits may be exceeded.

Reactive

RQ. lb

TPQ, lb

Waste Disposal:

Chronic

Key: Sec 313

Sec 302 RQ

TPQ

COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.

CAS NO.

Acute

naredient

None

Dispose through a licensed waste disposal company. Follow federal, state an local regulation.

Pressure

Sec 302

SPECIAL PRECAUTIONS AND COMMENTS

Store in tightly closed containers in an dry cool place, away from sources of hea Storage Requirements: ignition or strong oxidizers. Ground and bond all transfer and storage equipmen and equip with self closing valves, pressure vacuum bungs and flame arresters

Fire

SARA TITLE III INFORMATION

v	X		
^	^		

%, WT

= Toxic Chemicals, Section 313

= Reportable Quantity of EHS

Sec 313

SARA Hazardous Substances

CALIFORNIA PROPOSITION 65 WARNING

= Extremely Hazardous Substances (EHS)

= Threshold Planning Quantity of EHS

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be four in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potenti for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantitie

Read and follow directions and use care when handling these petroleum products. THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID, FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MAKE AS

TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND